

# YL-125



## TECHNICAL SPECIFICATIONS

<b>Max hose size</b>	6"
<b>Crimping force (kN):</b>	4000
<b>Max crimping Ø (mm):</b>	202
<b>Max opening (mm):</b>	die diameter + 125
<b>Standard motor:</b>	5,5kW 400V 3-Ph
Different voltage versions available	
<b>Control</b>	Digital control
<b>Master dies opening / Length (mm):</b>	335/116
<b>Crimping range (mm):</b>	10 - 202
<b>Weight (kg)</b>	3000 (without oil)

## STANDARD DIE SETS

<b>Size</b>	<b>Range (mm)</b>	<b>Length</b>
<b>32-10</b>	10-13	55
<b>32-13</b>	13-16	55
<b>32-16</b>	16-19	55
<b>32-19</b>	19-22	55
<b>32-22</b>	22-26	55
<b>32-26</b>	26-30	55
<b>32-30</b>	30-34	75
<b>32-34</b>	34-39	75
<b>32-39</b>	39-45	75
<b>32-45</b>	45-52	90
<b>32-52</b>	52-57	90
<b>32-57</b>	57-64	90
<b>32-64</b>	64-69	100
<b>32-69</b>	69-74	100
<b>32-74</b>	74-78	110
<b>32-78</b>	78-87	110
<b>125-84</b>	84-92	116
<b>125-92</b>	92-100	116
<b>125-100</b>	100-108	116
<b>125-108</b>	108-116	116
<b>125-116</b>	116-126	116
<b>125-126</b>	126-136	116
<b>125-136</b>	136-146	116
<b>125-146</b>	146-156	116
<b>125-156</b>	156-166	116
<b>125-166</b>	166-178	116
<b>125-178</b>	178-190	116
<b>125-190</b>	190-202	116

<b>Dimensions (LxWxH mm)</b>	1050 x 1300 x 1750
<b>Die sets</b>	Standard
	10-13-16-19-22-26-30-34-39-45-52-57-64-69-74-78-84-92-100-108-116-126-136-146-156-166-178-190
<b>Quick Change-set</b>	Standard
<b>Back stop device</b>	Standard
<b>Foot pedal</b>	Standard

**WWW.DHYDRO.COM**