

# SM 32 M



**STANDARD DIE SETS**

	<b>RANGE (mm)</b>	<b>LENGHT</b>
<b>32-06</b>	6-16	40
<b>32-08</b>	8-18	40
<b>32-11</b>	11-21	40
<b>32-14</b>	14-24	40
<b>32-17</b>	17-27	40
<b>32-20</b>	20-30	45
<b>32-23</b>	23-33	50
<b>32-26</b>	26-36	50
<b>32-31</b>	31-41	55
<b>32-34</b>	34-44	60
<b>32-39</b>	39-49	60
<b>32-43</b>	43-53	65
<b>32-45</b>	45-55	65
<b>32-51*</b>	51-61	65

**TECHNICAL SPECIFICATIONS**

<b>Max hose size</b>	1 1/2" 1SN, 1 1/4" 2SN, 1" 4SP
<b>Crimping force (kN):</b>	1450
<b>Max crimping Ø (mm):</b>	61
<b>Max opening (mm):</b>	die diameter + 20
<b>Standard motor:</b>	2,2 kW 380V 3-Ph
Different voltage versions available	
<b>Control</b>	Micrometer
<b>Master dies opening / Length(mm):</b>	95/66
<b>Crimping range (mm):</b>	6 – 61
<b>Weight (kg)</b>	94 (without oil)
<b>Dimensions (LxWxH mm)</b>	710 x 360 x 600
<b>Quick Change-set</b>	Optional
<b>Stand for machine</b>	Optional

\* Max. ferrule diameter before crimping 61 mm

**OPTIONS**



Quick Change Set: including storage rack & handle



Solid stand with ability to mount the Quick Change set and machine